

B077R22

**Portable pre-filter unit (p<sub>e</sub> 50 bar)**

Dry filter filled with molecular sieve and aluminium oxide Al<sub>2</sub>O<sub>3</sub> combined with particle filter

**For filtering moisture, solid and gaseous decomposition products**



**Standard version**

- dry filter (water absorption capacity: 175 g at a dew point of -36 °C)
- particle filter 1 µm
- DILO couplings DN20
- safety valve (p<sub>e</sub> 50 bar)
- gauge NG63

**Advantages & functions**

- replaceable filter cartridges
- DILO couplings DN20

**Technical data**

Dimensions (W x H x D)	210 x 200 x 780 mm
Weight	13.5 kg
Ambient temperature	0 to +45 °C
Operating temperature	0 to +45 °C
Storage temperature	-20 to +60 °C

## Optional accessories

---

6-1017-R020	2 meter long rubber hose DN20 with coupling tongue part on both ends
6-1017-R050	5 m long rubber hose DN20 with DILO coupling tongue part DN20 on both ends
6-1365-R020	2 meter long wire braided hose DN20 with coupling tongue part on both ends PN 64 bar
6-1365-R050	5 m long wire braided hose DN20 with DILO coupling tongue part on both ends PN 64 bar
B077-10	Spare filter cartridge for dry filter
B077-06	Spare filter cartridge for particle filter
3-781-R030	Aluminium box for B007R11

## Packaging

---

3-763-R003-C	Packing for B077R22
--------------	---------------------

