

Z446R04

Hose reel for three gas compartment hoses

Mobile unit for hose reeling

The hose reel has been specially designed for optimising SF₆ gas handling and for keeping hoses tidy in GIS production. The hose distributor allows to connect several gas compartments at the same time which can be treated by means of an SF₆ maintenance device. As the unit is equipped with four steerable rollers it can easily be transported to the desired location. The hose reel is of robust construction and can store up to eight hoses.



Standard version

- Reel with four steerable rollers
- Optionally available with hoses

Advantages & functions

- Stable steel frame
- Steerable rollers allow easy transport
- With 3, 6 or 8 DN20 hoses available as option
- DN40 connecting hose to gas handling plant
- Different hose lengths are available

Technical data

Dimensions (W x H x D)	700 x 1100 x 700 mm
Weight	100 kg

Optional accessories

SM0140L05000	5 m long wire braided hose DN40 (from gas handling plant to hose reel)
SM0140L10000	10 m long wire braided hose DN40 (from gas handling plant to hose reel)
VK/F-01/40 E	Coupling tongue part DN40 (for DN40 hose)
GS0120L02000	2 m long rubber hose DN20 (from hose reel to gas compartment)
GS0120L03000	3 m long rubber hose DN20 (from hose reel to gas compartment)
GS0120L04000	4 m long rubber hose DN20 (from hose reel to gas compartment)
GS0120L05000	5 m long rubber hose DN20 (from hose reel to gas compartment)
GS0120L06000	6 m long rubber hose DN20 (from hose reel to gas compartment)
SM0120L02000	2 m long wire braided hose DN20 (from hose reel to gas compartment) PN 40 bar
SM0120L03000	3 m long wire braided hose DN20 (from hose reel to gas compartment) PN 40 bar
SM0120L04000	4 m long wire braided hose DN20 (from hose reel to gas compartment) PN 40 bar
SM0120L05000	5 m long wire braided hose DN20 (from hose reel to gas compartment) PN 40 bar
SM0120L06000	6 m long wire braided hose DN20 (from hose reel to gas compartment) PN 40 bar
VK/F-02/20 P	Coupling tongue part DN20 (for DN20 hose)
3-1121-R003	DN20 Quick coupling

Packaging

3-1001-R005-C	Packing for K091R54 / Z446R..
---------------	-------------------------------

